

EV-4450AF

desktop video presenter



- 1/3" 470,000 pixels IT CCD
- Powerful 18x optical zoom plus 2x digital zoom
- Max. 420x310 mm wide shooting area
- Built-in base light for transparency/slide film viewing
- Wireless remote control and mouse
- Simple and easy to operate
- Auto focus
- Nega/Posi conversion
- Colour/B&W selection
- User friendly OSD menu
- Flat stage body with foldable camera arm and carrying handle

EV4450AF leaflet -32.94k (ev4450af_01.pdf)

SPECIFICATIONS

Image pick-up element	1/3 " IT CCD
Total picture elements	795 (H) x 596 (V), 470,000
Effective picture elements	752 (H) x 582 (V)
Resolution (Video)	> 470 (H) x 380 (V)
Close-up lens	O
Optical zoom	18x
Digital zoom	2x (can be scrolled by mouse)
Lens	4,7 - 84,6 mm, F=2,1-2,4
Focusing	Auto/Manual
Shooting area (Minimum)	26 x 20 mm
Shooting area (Maximum)	420 x 310 mm
Iris	Auto (with level adjustment / Manual)
White balance	Auto / One Push
Nega/Posi conversion	O
Colour/B&W selection	O
Gamma adjustment	----
Freeze function	----
On Screen Display (OSD)	O
Image rotation	----
Camera head rotation	O
Sync. system	Internal / External
Scrolling	O
Edge Enhancement	O
User pre-set	2 Settings
Input selection	Internal / AV1 / AV2
C-Video input	O
S-Video input	O
Mic. input	O
Audio input	O
C-Video output	PAL
S-Video output	PAL
12VDC out terminal	O

RS-232C control terminal	DSUB 9 Pin
USB terminal	----
Lighting unit	Upper light / Base light
Mouse	O
Wireless remote controller	O
Power source	AC100-240 V, 50/60 Hz
Power consumption	0,3-0,5 A
Dimensions (WxDxH) mm	766 x 549 x 602 (Set-up), 533 x 449 x 190 (Folded)
Weight	10 kg

Weight and Dimensions are approximate. Design and specifications are subject to change without prior notice.

ELMO EUROPE GMBH - Neanderstr. 18 - 40233 Duesseldorf - Germany
Phone: ++49-211-386 47-0 / FAX: ++49-211-376 630 / E-Mail: info@elmoeurope.de